

| | |
|-------------------------------------|--------------|
| JOYSTICK | 83-87, 92-94 |
| KEYBOARD | 33-34, 79-81 |
| LIGHT EMITTING DIODE (LED) | 73 |
| LOGIC | 9 |
| LOW | 97 |
| MACHINE CODE | 98 |
| MEMORY | 98 |
| MICROPROCESSORS | 23 |
| MULTIPLXED | 27 |
| NON-MASKABLE INTERRUPT (NMA) | 26, 59 |
| OPERATING SYSTEM | 9 |
| OUT | 76 |
| OUTPUT | 73 |
| PARALLEL INPUT/OUTPUT CIRCUIT | 73-76 |
| PATCH | 41 |
| PERIPHERAL | 98 |
| POWER SUPPLY | 15-19 |
| PRECAUTIONS | 7 |
| RANDOM ACCESS MEMORY (RAM) | 11, 27, 98 |
| READ ONLY MEMORY (ROM) | 11, 31, 98 |
| REFERENCES | 99 |
| REFRESH | 24, 98 |
| REGULATOR | 15 |
| RESET | 26, 61 |
| ROW ADDRESS STROBE (RAS) | 27 |
| SOUND | 43 |
| STATE | 98 |
| STATIC RAM | 27 |
| SYSTEM | 9 |
| TRANSUDUCER | 89, 98 |
| TRISTATE | 98 |
| TRUE | 23 |
| TUNING | 55 |
| UNCOMMITTED LOGIC ARRAY (ULA) | 37, 56 |
| VIDEO CIRCUIT | 53 |
| VIDEO MEMORY | 27 |
| WAIT | 24 |
| Z80 CPU | 23 |
| Z80A CPU | 23 |
| Z80B CPU | 23 |
| Z80A PIO | 26 |
| ZENER DIODE | 15, 98 |

INDEX

| | | |
|-------------------------------------|---------|----------------|
| ACTIVE LOW | Page No | 23 |
| ADDING YOUR OWN CIRCUITS | | 73 |
| ADDRESS BUS | | 23, 59 |
| ADJUSTMENTS | | 55-57 |
| AMPLIFIER | | 44 |
| ANALOGUE TO DIGITAL CONVERTER | | 89-94 |
| BASIC ROM | | 31 |
| BEEP | | 44 |
| BIDIRECTIONAL | | 97 |
| BINARY | | 9, 97 |
| BIT | | 97 |
| BUSES | | 9 |
| BUZZER | | 43-44 |
| BYTE | | 97 |
| CASSETTE I/O | | 43-44 |
| CHIP | | 97 |
| CLOCK | | 23, 43 |
| COLOUR MONITORS | | 53 |
| COLUMN ADDRESS STROBE (CAS) | | 27 |
| COMPONENTS | | 7, 97 |
| CONTROL BUS | | 11 |
| CPU | | 9-11, 97 |
| CRASH | | 97 |
| CRYSTAL | | 97 |
| DATA BUS | | 24, 97 |
| DEAD COCKROACH | | 41 |
| DECOUPLING CAPACITORS | | 19 |
| DIAGNOSING FAULTS | | 62-63 |
| DRAWING PROGRAM | | 94 |
| DYNAMIC RAM | | 27 |
| EAR SOCKET | | 43-44 |
| EDGE CONNECTOR | | 59-61 |
| EXPANSION MEMORY | | 47 |
| EXPERIMENTS | | 76 |
| FALSE | | 23 |
| FAULTS | | 62-63 |
| GREY SCALE | | 55-57 |
| HALT | | 24, 68 |
| HEATSINK | | 15, 97 |
| HEXADECIMAL | | 97 |
| HIGH | | 97 |
| IN | | 78 |
| INPUT | | 73 |
| INTERRUPT | | 24, 59, 73, 97 |